

NOVUS Enregistreur IP Novus 32 flux dont 16 POE 5 MégaPixels Série 6000

ER6432-IPPOE/F

16 x Ethernet PoE - RJ-45 interface, 10/100 Mbit/s • Video and audio channels: 32 • Supported protocols: ONVIF, RTSP • Recording speed up to 960 fps at 3840 x 2160 • Supports resolution up to 3840 x 2160 • Recorded stream size: 256 Mb/s in total from all cameras • Internal HDDs mount: 4 • Monitor outputs: 2 (HDMI (4K UltraHD), VGA) • RACK mount • Face recognition

NOVUS



Caractéristiques Principales



Vue connecteurs

Données Techniques

Caméras IP	Jusqu'à 32 canaux résolution 3840 x 2160 (video + audio)
Compression	H.264, H.264+, H.265, H.265 Smart
Dualstreaming Support	Oui
Fisheye Support	yes, 3000/6000 IP series cameras
Recording Speed	960 fps (32 x 30 fps for 3840 x 2160)
Stream Size	256 Mb/s in total from all cameras
Recording Mode	time-lapse, triggered by: manual, alarm input, motion detection
Prealarm/Postalarm	up to 5 s/up to 600 s
Playback Speed	480 fps (16 x 30 fps)
Recorded Data Search	by date/time, events, motion in a defined area, related to face recognition
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI, RPAS (player included)
Capacité de stockage	jusqu'à 4 x HDD 3,5" 14 TB SATA
Total Internal Capacity	56 TB
Internal Alarm Input/Output	16/4 relay type

Produits Conseillés



INTEGRDD

Intégration disque dur + mise en route DVR/NVR



PURPLE-8TO

Western Digital Purple Disque Dur HDD 3,5" SATA 8To



PURPLE-10TO

Western Digital Purple Disque Dur HDD 3,5" SATA 10To



EVA6

ETIQUETTE VIDEOPROTECTION A6



EVA4

ETIQUETTE VIDEOPROTECTION A4